


*** SECTION 1: Identification of the substance/mixture and of the company/undertaking****· 1.1 Product identifier****· Trade name: 9230 Multilight Filler****· Article number:** FRL1159**· UFI:** 7410-R0RQ-7004-EEA6**· 1.2 Relevant identified uses of the substance or mixture and uses advised against****· Sector of Use**

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· Product category PC9b Fillers, putties, plasters, modelling clay**· Process category** PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities**· Environmental release category** ERC2 Formulation into mixture**· Article category** AC1 Vehicles**· Application of the substance / the mixture** Surface protection**· 1.3 Details of the supplier of the safety data sheet****· Manufacturer/Supplier:** FRL Chemie Gmbh, Theresienhöhe 28,
80339 Munich, Germany
MADE IN EU - T. +498926201297 - E. info@vollchem.com
web:www.vollchem.com**· Further information obtainable from:** FRL Chemie Gmbh, Theresienhöhe 28,
80339 Munich, Germany
MADE IN EU - T. +498926201297 - E. info@vollchem.com
web:www.vollchem.com**· 1.4 Emergency telephone number:**

Regional Medicines and Poisons Information Centre NI

Pharmacy Department, Royal Hospital Suite

Grosvenor Road Belfast

Telephone: +44 28 90 63 2032

Fax: +44 28 90 24 80 30

Emergency telephone: 844 892 0111

E-mail address: nirdic.nirdic@belfasttrust.hscni.net

Members of the public seeking specific information on poisons should contact:

In England and Wales: NHS 111 - dial 111

In Scotland: NHS 24 - dial 111

Trade name: 9230 Multilight Filler

*** SECTION 2: Hazards identification****2.1 Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008**

GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 health hazard

Repr. 2 H361d Suspected of damaging the unborn child.

STOT RE 1 H372 Causes damage to the hearing organs through prolonged or repeated exposure. Route of exposure: Inhalation.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

2.2 Label elements**Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms

GHS02 GHS07 GHS08

Signal word Danger**Hazard-determining components of labelling:**

styrene

Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H361d Suspected of damaging the unborn child.

H372 Causes damage to the hearing organs through prolonged or repeated exposure. Route of exposure: Inhalation.

Continue on page 3

Trade name: 9230 Multilight Filler

Precautionary statements

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P241 Use explosion-proof [electrical/ventilating/lighting] equipment.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Labelling of packages where the contents do not exceed 125 ml**Hazard pictograms**

GHS02 GHS07 GHS08

Signal word Danger**Hazard-determining components of labelling:**

styrene

Hazard statements

- H361d Suspected of damaging the unborn child.
- H372 Causes damage to the hearing organs through prolonged or repeated exposure. Route of exposure: Inhalation.

Precautionary statements

- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards**Results of PBT and vPvB assessment**





This product contains no substance that is considered to be persistent, bioaccumulating or non toxic (PBT). This mixture contains no substance that is considered to be very persistent or very bioaccumulating (vPvB).

PBT: Not applicable**vPvB:** Not applicable

SECTION 3: Composition/information on ingredients**3.2 Chemical characterisation: Mixtures****Description:** Mixture of hazardous substances listed below with nonhazardous additions.

Continue on page 4

Trade name: 9230 Multilight Filler

Dangerous components:		
CAS: 100-42-5 EINECS: 202-851-5 Index number: 601-026-00-0 RTECS: WL 3675000 Reg.nr.: 01-2119457861-32-0011 01-2119457861-32-0009	styrene  Flam. Liq. 3, H226  Repr. 2, H361d; STOT RE 1, H372  Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319 Note: D	15-<20%
CAS: 13463-67-7 EINECS: 236-675-5 Index number: 022-006-00-2	titanium dioxide  Carc. 2, H351 Note: V, W, 10	1-<5%

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information: Immediately remove any clothing soiled by the product.

After inhalation: In case of unconsciousness place patient stably in side position for transportation.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. Remove contact lenses in case of eye contamination and irrigate copiously with clean water for at least 15 minutes trying to hold the eye lids open.

After swallowing: If symptoms persist consult doctor.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

5.3 Advice for firefighters

Firefighters should always use protective equipment and breathing apparatus when handling fire coming from these products

Continue on page 5

Trade name: 9230 Multilight Filler

5.6 Fire and explosion Hazards**Speial protective equipment and fire fighting procedures:**

Mouth respiratory protective device.

Firefighters should wear full protective flameproof clothing and self contained breathing apparatus for the firefighter if necessary. In the event of any fire try cool down the tanks with water spray. If possible do not allow the water used by firefighters to enter the drains or come in any contact with the water supply lines for the public. Always seek as appropriate.

Additional information Collect contaminated fire fighting water separately. It must not enter the sewage system.

*** SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures**

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

*** SECTION 7: Handling and storage****7.1 Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

7.2 Conditions for safe storage, including any incompatibilities**Storage:**

Requirements to be met by storerooms and receptacles: No special requirements.

Information about storage in one common storage facility: Not required

Further information about storage conditions: Keep container tightly sealed.

Continue on page 6

Trade name: 9230 Multilight Filler

· **7.3 Specific end use(s)** No further relevant information available.

* **SECTION 8: Exposure controls/personal protection**

· **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

100-42-5 styrene

WEL	Short-term value: 1080 mg/m ³ , 250 ppm Long-term value: 430 mg/m ³ , 100 ppm
-----	--

· **Regulatory information** WEL: EH40/2020

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the eyes and skin.

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
 Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Continue on page 7

Trade name: 9230 Multilight Filler

· **For the permanent contact in work areas without heightened risk of injury (e.g. Laboratory) gloves made of the following material are suitable:**

The breakthrough time of gloves is unknown for this product itself. The glove material that can be used is recommended on the basis of the different substances in the preparation.

· **For the permanent contact gloves made of the following materials are suitable:** Fluorocarbon rubber (Viton)

· **For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:**

Rubber gloves

· **Eye protection:**



Tightly sealed goggles

· **Body protection:** Protective work clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

· **Appearance:**

Form:	Pasty
Colour:	According to product specification
· Odour:	Characteristic
· Odour threshold:	Not determined

· **pH-value:** Mixture is non-soluble (in water).

Change in condition

Melting point/freezing point:	Undetermined
Initial boiling point and boiling range:	145.2 °C (100-42-5 styrene)

· **Flash point:** 23 - 60 °C

· **Flammability** Flammable.

· **Autoignition temperature:** 480 °C (100-42-5 styrene)

· **Decomposition temperature:** Not determined

Continue on page 8

Trade name: 9230 Multilight Filler

· Ignition temperature:	Product is not selfigniting.
· Explosive properties:	Risk of explosion by shock, friction, fire or other sources of ignition.
· Explosion limits:	
Lower:	1.2 Vol % (100-42-5 styrene)
Upper:	8.9 Vol % (100-42-5 styrene)
· Vapour pressure at 20 °C:	6 hPa (100-42-5 styrene)
· Vapour pressure at 50 °C:	35 hPa
· Density at 20 °C:	1.2 g/cm ³
· Relative density	Not determined
· Vapour density	Not determined
· Evaporation rate	Not determined
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined
· Viscosity:	
Dynamic:	Not determined
Kinematic:	Not determined
· Solvent content:	
Organic solvents:	17.3 %
VOC (EC)	208.5 g/l
Solids content (volume):	82.0 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.

Continue on page 9

Trade name: 9230 Multilight Filler

- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

471-34-1 calcium carbonate

Oral	LD50	6,450 mg/kg (rat)
------	------	-------------------

100-42-5 styrene

Oral	LD50	5,000 mg/kg (rat)
Inhalative	LC50/4 h	24 mg/l (rat)

13463-67-7 titanium dioxide

Oral	LD50	>20,000 mg/kg (rat)
Dermal	LD50	>10,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>6.82 mg/l (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation**
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Additional toxicological information:**
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity**
Suspected of damaging the unborn child.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure**
Causes damage to the hearing organs through prolonged or repeated exposure. Route of exposure: Inhalation.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

Trade name: 9230 Multilight Filler

* **SECTION 12: Ecological information**

· **12.1 Toxicity**

· **Aquatic toxicity:**

This product is not toxic for the aquatic life. Nevertheless do not dispose the product or any cleaning solvents used along with this product into the sea

· **12.2 Persistence and degradability**

This product contains polyesteric molecules and organic solvents and is not known to be bioaccumulative. It can be considered as biodegradable in small quantities. In case of disposal, it should be treated as a hazardous material and should be disposed accordingly. Do not just throw it away

· **12.3 Bioaccumulative potential** No further relevant information available.

· **12.4 Mobility in soil** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
 Do not allow product to reach ground water, water course or sewage system.
 Danger to drinking water if even small quantities leak into the ground.

· **12.5 Results of PBT and vPvB assessment**

· **PBT:** This product contains no substance that is considered to be persistent, bioaccumulating or non toxic (PBT).

· **vPvB:** This mixture contains no substance that is considered to be very persistent or very bioaccumulating (vPvB).

· **12.6 Other adverse effects** No further relevant information available.

* **SECTION 13: Disposal considerations**

· **13.1 Waste treatment methods**

· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **European waste catalogue**



HP3	Flammable
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP7	Carcinogenic
HP10	Toxic for reproduction

· **Uncleaned packaging:**

· **Recommendation:** Disposal must be made according to official regulations.

Trade name: 9230 Multilight Filler

*** SECTION 14: Transport information**

· 14.1 UN-Number · ADR, IMDG, IATA	UN1263
· 14.2 UN proper shipping name · ADR · IMDG, IATA	UN1263 PAINT RELATED MATERIAL PAINT RELATED MATERIAL
· 14.3 Transport hazard class(es) · ADR	
	
· Class · Label	3 (F1) Flammable liquids. 3
· IMDG, IATA	
	
· Class · Label	3 Flammable liquids. 3
· 14.4 Packing group · ADR, IMDG, IATA	III
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user · Hazard identification number (Kemler code): · EMS Number: · Stowage Category	Warning: Flammable liquids. 30 F-E, <u>S-E</u> A
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable

Continue on page 12

Trade name: 9230 Multilight Filler

· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Transport category	3
· Tunnel restriction code	D/E
· IMDG	
· Limited quantities (LQ)	500 ml
· Excepted quantities (EQ)	Code: E3 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 300 ml
· UN "Model Regulation":	UN 1263 PAINT RELATED MATERIAL, 3, III

* **SECTION 15: Regulatory information**
 •3Y

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
None of the ingredients is listed.
· Poisons Act
· Regulated explosives precursors
None of the ingredients is listed.
· Regulated poisons
None of the ingredients is listed.
· Reportable explosives precursors
None of the ingredients is listed.
· Reportable poisons
None of the ingredients is listed.
· Labelling according to Regulation (EC) No 1272/2008
The product is classified and labelled according to the GB CLP regulation.

Continue on page 13

Trade name: 9230 Multilight Filler

· **Hazard pictograms**



· **Signal word** Danger

· **Hazard-determining components of labelling:**

styrene

· **Hazard statements**

- H226 Flammable liquid and vapour.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H361d Suspected of damaging the unborn child.
- H372 Causes damage to the hearing organs through prolonged or repeated exposure. Route of exposure: Inhalation.

· **Precautionary statements**

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P241 Use explosion-proof [electrical/ventilating/lighting] equipment.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **Seveso category** P5c FLAMMABLE LIQUIDS

· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t

· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t

· **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II
None of the ingredients is listed.

· **REGULATION (EU) 2019/1148**

· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))
None of the ingredients is listed.

Continue on page 14

Trade name: 9230 Multilight Filler

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

108-88-3	toluene	3
----------	---------	---

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

108-88-3	toluene	3
----------	---------	---

15.2 Chemical safety assessment: A Chemical Safety Assessment has been carried out.

SECTION 16: Other information

This information is based on our current knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases


- H226 Flammable liquid and vapour.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H351 Suspected of causing cancer.
- H361d Suspected of damaging the unborn child.
- H372 Causes damage to organs through prolonged or repeated exposure.

Classification according to Regulation (EC) No 1272/2008

Flammable liquids	Bridging principles
Skin corrosion/irritation Serious eye damage/irritation Reproductive toxicity Specific target organ toxicity (repeated exposure)	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Department issuing SDS: Department of Quality Control

Contact:

 FRL Chemie GmbH, Theresienhöhe 28,
 80339 Munich, Germany
 MADE IN EU - T. +498926201297 - E. info@vollchem.com
 web:www.vollchem.com

*** Data compared to the previous version altered.**

Trade name: 9230 Multilight Filler

*** Annex: Exposure scenario 1****· Short title of the exposure scenario****· Sector of Use**

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· Product category PC9b Fillers, putties, plasters, modelling clay**· Process category** PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities**· Article category** AC1 Vehicles**· Environmental release category** ERC2 Formulation into mixture**· Description of the activities / processes covered in the Exposure Scenario**

See section 1 of the annex to the Safety Data Sheet.

· Conditions of use According to directions for use.**· Duration and frequency**

5 workdays/week.

Frequency of use:

· Physical parameters

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

· Physical state Fluid**· Concentration of the substance in the mixture** The substance is main component.**· Used amount per time or activity**

According to directions for use.

Smaller than 100 g per application.

· Other operational conditions**· Other operational conditions affecting environmental exposure** No special measures required.**· Other operational conditions affecting worker exposure**

Avoid contact with eyes.

Avoid contact with the skin.

Do not breathe gas/vapour/aerosol.

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

· Other operational conditions affecting consumer exposure No special measures required.**· Other operational conditions affecting consumer exposure during the use of the product**

Not applicable

Continue on page 16

Trade name: 9230 Multilight Filler

· Risk management measures**· Worker protection****· Organisational protective measures**

No special measures required.

Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.

· Technical protective measures

Ensure that suitable extractors are available on processing machines

Provide explosion-proof electrical equipment.

· Personal protective measures

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Avoid contact with the eyes.

Tightly sealed goggles

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Pregnant women should strictly avoid inhalation or skin contact.

· Measures for consumer protection

Ensure adequate labelling.

Observe consumer information and advice on safe use.

· Environmental protection measures**· Water**

No special measures required.

Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point.

· Soil The product is only processed over the concrete collecting basin.**· Disposal measures**

Disposal must be made according to official regulations.

Ensure that waste is collected and contained.

· Disposal procedures

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Waste type Partially emptied and uncleaned packaging

Continue on page 17

Trade name: 9230 Multilight Filler

· **Exposure estimation**

· **Consumer**

Not relevant for this Exposure Scenario.

This product is to be used by professional technicians only.

· **Guidance for downstream users**

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.

Trade name: 9230 Multilight Filler

*** Annex: Exposure scenario 2****· Short title of the exposure scenario****· Product category** PC9b Fillers, putties, plasters, modelling clay**· Description of the activities / processes covered in the Exposure Scenario**

See section 1 of the annex to the Safety Data Sheet.

· Conditions of use According to directions for use.**· Duration and frequency** Frequency of use:**· Physical parameters**

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

· Physical state Fluid**· Concentration of the substance in the mixture** Raw material.**· Other operational conditions****· Other operational conditions affecting environmental exposure** No special measures required.**· Other operational conditions affecting worker exposure**

Avoid contact with eyes.

Avoid contact with the skin.

Do not breathe gas/vapour/aerosol.

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

· Other operational conditions affecting consumer exposure No special measures required.**· Other operational conditions affecting consumer exposure during the use of the product**

Not applicable

· Risk management measures**· Worker protection****· Organisational protective measures**

Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.

· Technical protective measures

Provide explosion-proof electrical equipment.

Ensure that suitable extractors are available on processing machines

· Personal protective measures

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Avoid contact with the eyes.

Pregnant women should strictly avoid inhalation or skin contact.

Continue on page 19

Trade name: 9230 Multilight Filler

Tightly sealed goggles

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Measures for consumer protection**

Ensure adequate labelling.

Observe consumer information and advice on safe use.

· **Environmental protection measures**

· **Water**

Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point.

· **Soil** The product is only processed over the concrete collecting basin.

· **Disposal measures** Ensure that waste is collected and contained.

· **Disposal procedures**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Waste type** Partially emptied and uncleaned packaging

· **Exposure estimation**

· **Consumer**

Not relevant for this Exposure Scenario.

This product is to be used by professional technicians only.

· **Guidance for downstream users**

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.