

---


**\* SECTION 1: Identification of the substance/mixture and of the company/undertaking****· 1.1 Product identifier****· Trade name: 9310 2K HS Primer****· Article number:** FRL1168**· UFI:** QW10-90Y8-Y00K-DGJS**· 1.2 Relevant identified uses of the substance or mixture and uses advised against****· Life cycle stages** F Formulation or re-packing**· Sector of Use**

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites


SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

**· Product category** PC9b Fillers, putties, plasters, modelling clay**· Process category**

PROC9 Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

**· Environmental release category** ERC2 Formulation into mixture**· Article category** AC1 Vehicles**· Technical function** Other**· Application of the substance / the mixture** Surface protection**· 1.3 Details of the supplier of the safety data sheet****· Manufacturer/Supplier:**

FRL Chemie Gmbh, Theresienhöhe 28,  
80339 Munich, Germany  
MADE IN EU - T. +498926201297 - E. info@vollchem.com  
web:www.vollchem.com

**· Further information obtainable from:**

FRL Chemie Gmbh, Theresienhöhe 28,  
80339 Munich, Germany  
MADE IN EU - T. +498926201297 - E. info@vollchem.com  
web:www.vollchem.com

**· 1.4 Emergency telephone number:**

Members of the public seeking specific information on poisons should contact:

In England and Wales: NHS 111 - dial 111

In Scotland: NHS 24 - dial 111

Regional Medicines and Poisons Information Centre NI

Pharmacy Department, Royal Hospital Suite

Grosvenor Road Belfast

Telephone: +44 28 90 63 2032

---

**Trade name: 9310 2K HS Primer**

---

Fax: +44 28 90 24 80 30

Emergency telephone: 844 892 0111

E-mail address: nirdic.nirdic@belfasttrust.hscni.net

---

**SECTION 2: Hazards identification****2.1 Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008**

GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

**2.2 Label elements****Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the GB CLP regulation.

**Hazard pictograms**

GHS02 GHS07

**Signal word** Warning**Hazard statements**

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

**Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Additional information:**

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Continue on page 3

**Trade name: 9310 2K HS Primer**
**2.3 Other hazards**
**Results of PBT and vPvB assessment**

This product contains no substance that is considered to be persistent, bioaccumulating or non toxic (PBT). This mixture contains no substance that is considered to be very persistent or very bioaccumulating (vPvB).












· **PBT:** Not applicable.

· **vPvB:** Not applicable.

**SECTION 3: Composition/information on ingredients**
**3.2 Chemical characterisation: Mixtures**

· **Description:** Mixture of hazardous substances listed below with nonhazardous additions.

**Dangerous components:**

|  |   |          |
|--|---|----------|
| CAS: 1330-20-7<br>Index number: 601-022-00-9   | xylene<br> Flam. Liq. 3, H226<br> Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315   | ≥15-<20% |
| CAS: 13463-67-7<br>EINECS: 236-675-5<br>Index number: 022-006-00-2   | titanium dioxide<br> Carc. 2, H351<br>Note: V, W, 10   | 5-<10%   |
| CAS: 123-86-4<br>EINECS: 204-658-1<br>Index number: 607-025-00-1<br>RTECS: AF 7350000<br>Reg.nr.: 01-2119485493-29-007<br>01-2119485493-29-004<br>01-2119485493-29-003<br>01-2119485493-29-005<br>01-2119485493-29 | n-butyl ester<br> Flam. Liq. 3, H226<br> STOT SE 3, H336  | ≥1-<5%   |
| CAS: 64742-95-6<br>EINECS: 265-199-0<br>Index number: 649-356-00-4<br>Reg.nr.: 01-2119455851-35-0001   | Solvent naphtha (petroleum), light arom.<br> Flam. Liq. 3, H226<br> Asp. Tox. 1, H304<br> Aquatic Chronic 2, H411<br> Acute Tox. 4, H332; STOT SE 3, H335<br>STOT SE 3, H336<br>Note: H, P, 4 | ≥1-<2.5% |
| CAS: 872-50-4<br>EINECS: 212-828-1<br>Index number: 606-021-00-7<br>RTECS: UY 5790000  | 1-methyl-2-pyrrolidone<br> Repr. 1B, H360D<br> Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335<br>Specific concentration limit: STOT SE 3; H335: C ≥ 10 %  | ≥0-<0.3% |

Continue on page 4

---

**Trade name: 9310 2K HS Primer**

---

---

**SVHC**

872-50-4 | 1-methyl-2-pyrrolidone

**Additional information:** For the wording of the listed hazard phrases refer to section 16.

---

**SECTION 4: First aid measures****4.1 Description of first aid measures**

- General information:** Immediately remove any clothing soiled by the product.
- After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- After eye contact:** Rinse opened eye for several minutes under running water.
- After swallowing:** If symptoms persist consult doctor.

**4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

**4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

---

**SECTION 5: Firefighting measures****5.1 Extinguishing media****Suitable extinguishing agents:**CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.**For safety reasons unsuitable extinguishing agents:** Water with full jet**5.2 Special hazards arising from the substance or mixture** No further relevant information available.**5.3 Advice for firefighters**

Firefighters should always protective equipment and breathing apparatus when handling fire coming from these products

**5.6 Fire and explosion Hazards****Speial protective equipment and fire fighting procedures:**

Firefighters should wear full protective flameproof clothing and self contained breathing apparatus for the firefighter if necessary. In the event of any fire try cool down the tanks with water spray. If possible do not allow the water used by firefighters to enter the drains or come in any contact with the water supply lines for the public. Always seek as appropriate.

**Additional information** Collect contaminated fire fighting water separately. It must not enter the sewage system.

**Trade name: 9310 2K HS Primer**

\* **SECTION 6: Accidental release measures**

· **6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

· **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

· **6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· **6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

\* **SECTION 7: Handling and storage**

· **7.1 Precautions for safe handling** No special precautions are necessary if used correctly.

· **Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

· **7.2 Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:** No special requirements.

· **Information about storage in one common storage facility:** Not required.

· **Further information about storage conditions:** Keep container tightly sealed.

· **7.3 Specific end use(s)** No further relevant information available.

\* **SECTION 8: Exposure controls/personal protection**

· **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

**1330-20-7 xylene**

WEL Short-term value: 441 mg/m<sup>3</sup>, 100 ppm

Long-term value: 220 mg/m<sup>3</sup>, 50 ppm

Sk; BMGV

Continue on page 6

**Trade name: 9310 2K HS Primer**

**123-86-4 n-butyl ester**

|     |   |
|-----|---|
| WEL | Short-term value: 966 mg/m <sup>3</sup> , 200 ppm<br>Long-term value: 724 mg/m <sup>3</sup> , 150 ppm |
|-----|---|

**872-50-4 1-methyl-2-pyrrolidone**

|     |   |
|-----|---|
| WEL | Short-term value: 80 mg/m <sup>3</sup> , 20 ppm<br>Long-term value: 40 mg/m <sup>3</sup> , 10 ppm |
|     | Sk  |

· **Regulatory information** WEL: EH40/2020

· **Ingredients with biological limit values:**

**1330-20-7 xylene**

|      |  |
|------|--|
| BMGV | 650 mmol/mol creatinine<br>Medium: urine<br>Sampling time: post shift<br>Parameter: methyl hippuric acid |
|------|--|

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- Avoid contact with the skin.
- Avoid contact with the eyes and skin.

· **Respiratory protection:** Not required.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
 Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Continue on page 7

---

**Trade name: 9310 2K HS Primer**

---

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **For the permanent contact in work areas without heightened risk of injury (e.g. Laboratory) gloves made of the following material are suitable:**

The breakthrough time of gloves is unknown for this product itself. The glove material that can be used is recommended on the basis of the different substances in the preparation.

· **For the permanent contact gloves made of the following materials are suitable:** Fluorocarbon rubber (Viton)

· **For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:**

Rubber gloves

· **Eye protection:**



Tightly sealed goggles

· **Body protection:** Protective work clothing

---

\* **SECTION 9: Physical and chemical properties**

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· **Form:** Liquid

· **Colour:** Grey

· **Odour:** Characteristic

· **Odour threshold:** Not determined.

· **pH-value:** Mixture is non-soluble (in water).

· **Change in condition**

· **Melting point/freezing point:** Undetermined.

· **Initial boiling point and boiling range:** 140 °C (1330-20-7 xylene)

· **Flash point:** 23 - 60 °C

· **Flammability** Flammable.

· **Autoignition temperature:** >300 °C

Continue on page 8

---

**Trade name: 9310 2K HS Primer**


---

|  |  |
|--|--|
| · <b>Decomposition temperature:</b>              | Not determined.  |
| · <b>Ignition temperature:</b>                   | Product is not selfigniting.   |
| · <b>Explosive properties:</b>                   | Risk of explosion by shock, friction, fire or other sources of ignition. |
| · <b>Explosion limits:</b>                       |  |
| <b>Lower:</b>                                    | Not determined.  |
| <b>Upper:</b>                                    | Not determined.  |
| · <b>Vapour pressure:</b>                        | Not determined.  |
| · <b>Density at 20 °C:</b>                       | 1.624 g/cm <sup>3</sup>  |
| · <b>Bulk density:</b>                           | 1,624 kg/m <sup>3</sup>  |
| · <b>Relative density</b>                        | Not determined.  |
| · <b>Vapour density</b>                          | Not determined.  |
| · <b>Evaporation rate</b>                        | Not determined.  |
| · <b>Solubility in / Miscibility with water:</b> | Not miscible or difficult to mix.  |
| · <b>Partition coefficient: n-octanol/water:</b> | Not determined.  |
| · <b>Viscosity:</b>                              |  |
| <b>Dynamic at 20 °C:</b>                         | 140-145 mPas   |
| <b>Kinematic at 20 °C:</b>                       | 86-89 mm <sup>2</sup> /s   |
| · <b>Solvent content:</b>                        |  |
| <b>Organic solvents:</b>                         | ≥22.6-<22.7 %  |
| <b>VOC (EC)</b>                                  | ≥367.7-<367.9 g/l  |
| <b>Solids content (volume):</b>                  | 78.8 %   |
| · <b>9.2 Other information</b>                   | No further relevant information available.                               |

---

**SECTION 10: Stability and reactivity**

· **10.1 Reactivity** No further relevant information available.

Continue on page 9

---

**Trade name: 9310 2K HS Primer**


---

- **10.2 Chemical stability**
  - **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
  - **10.3 Possibility of hazardous reactions** No dangerous reactions known.
  - **10.4 Conditions to avoid** No further relevant information available.
  - **10.5 Incompatible materials:** No further relevant information available.
  - **10.6 Hazardous decomposition products:** No dangerous decomposition products known.
- 

**\* SECTION 11: Toxicological information**

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

|  |          |                       |
|--|----------|-----------------------|
| <b>LD/LC50 values relevant for classification:</b> |          |                       |
| <b>ATE (Acute Toxicity Estimates)</b>              |          |                       |
| Dermal   | LD50     | >12,012-≤12,013 mg/kg |
| Inhalative   | LC50/4 h | 59.8 mg/l             |

|                                   |      |                   |
|-----------------------------------|------|-------------------|
| <b>471-34-1 calcium carbonate</b> |      |                   |
| Oral                              | LD50 | 6,450 mg/kg (rat) |

|            |          |                      |
|------------|----------|----------------------|
| Oral       | LD50     | 4,300 mg/kg (rat)    |
| Dermal     | LD50     | 2,000 mg/kg (rabbit) |
| Inhalative | LC50/4 h | 11 mg/l (ATE)        |

|                         |          |                      |
|-------------------------|----------|----------------------|
| <b>1330-20-7 xylene</b> |          |                      |
| Oral                    | LD50     | 4,300 mg/kg (rat)    |
| Dermal                  | LD50     | 2,000 mg/kg (rabbit) |
| Inhalative              | LC50/4 h | 11 mg/l (ATE)        |

|      |      |                   |
|------|------|-------------------|
| Oral | LD50 | 6,450 mg/kg (rat) |
|------|------|-------------------|

|                                    |          |                        |
|------------------------------------|----------|------------------------|
| <b>13463-67-7 titanium dioxide</b> |          |                        |
| Oral                               | LD50     | >20,000 mg/kg (rat)    |
| Dermal                             | LD50     | >10,000 mg/kg (rabbit) |
| Inhalative                         | LC50/4 h | >6.82 mg/l (rat)       |

|            |          |                        |
|------------|----------|------------------------|
| Oral       | LD50     | >20,000 mg/kg (rat)    |
| Dermal     | LD50     | >10,000 mg/kg (rabbit) |
| Inhalative | LC50/4 h | >6.82 mg/l (rat)       |

|                               |          |                       |
|-------------------------------|----------|-----------------------|
| <b>123-86-4 n-butyl ester</b> |          |                       |
| Oral                          | LD50     | 13,100 mg/kg (rat)    |
| Dermal                        | LD50     | >5,000 mg/kg (rabbit) |
| Inhalative                    | LC50/4 h | >21 mg/l (rat)        |

|            |          |                       |
|------------|----------|-----------------------|
| Oral       | LD50     | 13,100 mg/kg (rat)    |
| Dermal     | LD50     | >5,000 mg/kg (rabbit) |
| Inhalative | LC50/4 h | >21 mg/l (rat)        |

|  |          |                    |
|--|----------|--------------------|
| <b>64742-95-6 Solvent naphtha (petroleum), light arom.</b> |          |                    |
| Oral   | LD50     | >6,800 mg/kg (rat) |
| Dermal   | LD50     | >3,400 mg/kg (rab) |
| Inhalative   | LC50/4 h | >10.2 mg/l (rat)   |

|            |          |                    |
|------------|----------|--------------------|
| Oral       | LD50     | >6,800 mg/kg (rat) |
| Dermal     | LD50     | >3,400 mg/kg (rab) |
| Inhalative | LC50/4 h | >10.2 mg/l (rat)   |

|  |          |                    |
|--|----------|--------------------|
| <b>64742-95-6 Solvent naphtha (petroleum), light arom.</b> |          |                    |
| Oral   | LD50     | >6,800 mg/kg (rat) |
| Dermal   | LD50     | >3,400 mg/kg (rab) |
| Inhalative   | LC50/4 h | >10.2 mg/l (rat)   |

|            |          |                    |
|------------|----------|--------------------|
| Oral       | LD50     | >6,800 mg/kg (rat) |
| Dermal     | LD50     | >3,400 mg/kg (rab) |
| Inhalative | LC50/4 h | >10.2 mg/l (rat)   |

Continue on page 10

**Trade name: 9310 2K HS Primer****872-50-4 1-methyl-2-pyrrolidone**

|        |      |                      |
|--------|------|----------------------|
| Oral   | LD50 | 3,914 mg/kg (rat)    |
| Dermal | LD50 | 8,000 mg/kg (rabbit) |

- **Primary irritant effect:**
- **Skin corrosion/irritation**  
Causes skin irritation.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Additional toxicological information:**
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

**\* SECTION 12: Ecological information**

- **12.1 Toxicity**
- **Aquatic toxicity:**  
This product is not toxic for the aquatic life. Nevertheless do not dispose the product or any cleaning solvents used along with this product into the sea
- **12.2 Persistence and degradability**  
This product contains polyesteric molecules and organic solvents and is not known to be bioaccumulative. It can be considered as biodegradable in small quantities. In case of disposal, it should be treated as a hazardous material and should be disposed accordingly. Do not just throw it away
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** This product contains no substance that is considered to be persistent, bioaccumulating or non toxic (PBT).
- **vPvB:** Not applicable.

Continue on page 11

**Trade name: 9310 2K HS Primer**

· **12.6 Other adverse effects** No further relevant information available.

\* **SECTION 13: Disposal considerations**

· **13.1 Waste treatment methods**

· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **European waste catalogue**

|     |              |
|-----|--------------|
| HP3 | Flammable    |
| HP7 | Carcinogenic |

· **Uncleaned packaging:**

· **Recommendation:** Disposal must be made according to official regulations.

\* **SECTION 14: Transport information**

· **14.1 UN-Number**

· **ADR, IMDG, IATA** UN1263

· **14.2 UN proper shipping name**

· **ADR** UN1263 PAINT  
 · **IMDG, IATA** PAINT

· **14.3 Transport hazard class(es)**

· **ADR**



· **Class** 3 (F1) Flammable liquids.  
 · **Label** 3

· **IMDG, IATA**



· **Class** 3 Flammable liquids.

**Trade name: 9310 2K HS Primer**

|   |  |
|---|--|
| · Label   | 3  |
| · 14.4 Packing group<br>· ADR, IMDG, IATA   | III  |
| · 14.5 Environmental hazards:   | Not applicable.  |
| · 14.6 Special precautions for user<br>· Hazard identification number (Kemler code):<br>· EMS Number:<br>· Stowage Category | Warning: Flammable liquids.<br>30<br>F-E, <u>S-E</u><br>A  |
| · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code   | Not applicable.  |
| · Transport/Additional information:   |  |
| · ADR   |  |
| · Limited quantities (LQ)   | 5L   |
| · Excepted quantities (EQ)  | Code: E1<br>Maximum net quantity per inner packaging: 30 ml<br>Maximum net quantity per outer packaging: 1000 ml |
| · Transport category  | 3  |
| · Tunnel restriction code   | D/E  |
| · IMDG  |  |
| · Limited quantities (LQ)   | 5L   |
| · Excepted quantities (EQ)  | Code: E1<br>Maximum net quantity per inner packaging: 30 ml<br>Maximum net quantity per outer packaging: 1000 ml |
| · IATA  |  |
| · Remarks:  | •3Y  |
| · UN "Model Regulation":  | UN 1263 PAINT, 3, III  |

\* SECTION 15: Regulatory information

•3Y

Continue on page 13

**Trade name: 9310 2K HS Primer****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

None of the ingredients is listed.

**Poisons Act****Regulated explosives precursors**

None of the ingredients is listed.

**Regulated poisons**

None of the ingredients is listed.

**Reportable explosives precursors**

None of the ingredients is listed.

**Reportable poisons**

None of the ingredients is listed.

**Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the GB CLP regulation.

**Hazard pictograms**

GHS02 GHS07

**Signal word** Warning**Hazard statements**

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

**Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Directive 2012/18/EU****Named dangerous substances - ANNEX I** None of the ingredients is listed.**Seveso category** P5c FLAMMABLE LIQUIDS

Continue on page 14

**Trade name: 9310 2K HS Primer**

- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3, 71, 72

· **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

· **REGULATION (EU) 2019/1148**

· **Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

· **Annex II - REPORTABLE EXPLOSIVES PRECURSORS**

None of the ingredients is listed.

· **Regulation (EC) No 273/2004 on drug precursors**

None of the ingredients is listed.

· **Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**

None of the ingredients is listed.

· **National regulations:**

· **Other regulations, limitations and prohibitive regulations**

· **Substances of very high concern (SVHC) according to UK REACH**

|          |                        |
|----------|------------------------|
| 872-50-4 | 1-methyl-2-pyrrolidone |
|----------|------------------------|

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has been carried out.

\* **SECTION 16: Other information**

This information is based on our current knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.

Continue on page 15

---

**Trade name: 9310 2K HS Primer**


---

- H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H351 Suspected of causing cancer.  
H360D May damage the unborn child.  
H411 Toxic to aquatic life with long lasting effects.

**Classification according to Regulation (EC) No 1272/2008**

|                           |  |
|---------------------------|--|
| Flammable liquids         | Bridging principles  |
| Skin corrosion/irritation | The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008. |

**Contact:**

 FRL Chemie Gmbh, Theresienhöhe 28,  
80339 Munich, Germany  
MADE IN EU - T. +498926201297 - E. info@vollchem.com  
web:www.vollchem.com

**\* Data compared to the previous version altered.**

---

**Trade name: 9310 2K HS Primer**

---

**\* Annex: Exposure scenario****· Short title of the exposure scenario****· Sector of Use**

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

**· Product category** PC9b Fillers, putties, plasters, modelling clay**· Process category**

PROC9 Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

**· Article category** AC1 Vehicles**· Environmental release category** ERC2 Formulation into mixture**· Technical function** Other**· Description of the activities / processes covered in the Exposure Scenario**

See section 1 of the annex to the Safety Data Sheet.

**· Conditions of use** According to directions for use.**· Duration and frequency** Frequency of use:**· Physical parameters**

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

**· Physical state** Fluid**· Concentration of the substance in the mixture** The substance is main component.**· Used amount per time or activity** Smaller than 100 g per application.**· Other operational conditions****· Other operational conditions affecting environmental exposure** No special measures required.**· Other operational conditions affecting worker exposure**

Avoid contact with the skin.

Do not breathe gas/vapour/aerosol.

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

Avoid contact with eyes.

**· Other operational conditions affecting consumer exposure** No special measures required.**· Other operational conditions affecting consumer exposure during the use of the product**

Not applicable.

**· Risk management measures****· Worker protection****· Organisational protective measures**

Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.

Continue on page 17

---

**Trade name: 9310 2K HS Primer**

---

**· Technical protective measures**

Provide explosion-proof electrical equipment.  
Ensure that suitable extractors are available on processing machines

**· Personal protective measures**

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Not required.

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Pregnant women should strictly avoid inhalation or skin contact.

Avoid contact with the eyes.

Tightly sealed goggles

**· Measures for consumer protection**

Ensure adequate labelling.

Observe consumer information and advice on safe use.

**· Environmental protection measures****· Water**

Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point.

· **Soil** The product is only processed over the concrete collecting basin.

· **Disposal measures** Ensure that waste is collected and contained.

**· Disposal procedures**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Waste type** Partially emptied and uncleaned packaging

**· Exposure estimation****· Consumer**

This product is to be used by professional technicians only.

Not relevant for this Exposure Scenario.

**· Guidance for downstream users**

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.