


*** SECTION 1: Identification of the substance/mixture and of the company/undertaking****· 1.1 Product identifier****· Trade name: Spray 9910 Underbody****· Article number:** FRL1186**· UFI:** KM30-E0S7-300G-MA72**· 1.2 Relevant identified uses of the substance or mixture and uses advised against****· Life cycle stages** IS Use at industrial Sites**· Sector of Use**

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· Product category PC9a Coatings and paints, thinners, paint removers**· Process category** PROC7 Industrial spraying**· Environmental release category** ERC5 Use at industrial site leading to inclusion into/onto article**· Article category** AC1 Vehicles**· Technical function** Other**· Application of the substance / the mixture** Surface protection**· 1.3 Details of the supplier of the safety data sheet****· Manufacturer/Supplier:**

FRL Chemie Gmbh, Theresienhöhe 28,
80339 Munich, Germany
MADE IN EU - T. +498926201297 - E. info@vollchem.com
web:www.vollchem.com

· Further information obtainable from:

FRL Chemie Gmbh, Theresienhöhe 28,
80339 Munich, Germany
MADE IN EU - T. +498926201297 - E. info@vollchem.com
web:www.vollchem.com

· 1.4 Emergency telephone number:

Regional Medicines and Poisons Information Centre NI

Pharmacy Department, Royal Hospital Suite

Grosvenor Road Belfast

Telephone: +44 28 90 63 2032

Fax: +44 28 90 24 80 30

Emergency telephone: 844 892 0111

E-mail address: nirdic.nirdic@belfasttrust.hscni.net

Trade name: Spray 9910 Underbody

Members of the public seeking specific information on poisons should contact:
In England and Wales: NHS 111 - dial 111
In Scotland: NHS 24 - dial 111

*** SECTION 2: Hazards identification****2.1 Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008**

GHS02 flame

Aerosol 1 H222 Extremely flammable aerosol.
 H229 Pressurised container: May burst if heated.



GHS08 health hazard

Repr. 2 H361d Suspected of damaging the unborn child.
STOT RE 2 H373 May cause damage to the central nervous system through prolonged or repeated exposure.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.
STOT SE 3 H336 May cause drowsiness or dizziness.
Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements**Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms

GHS02



GHS07



GHS08

Signal word Danger**Hazard-determining components of labelling:**

toluene

Naphtha (petroleum), hydrotreated light

Continue on page 3

— GB —

Trade name: Spray 9910 Underbody

Low boiling point hydrogen treated naphtha

· Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H315 Causes skin irritation.

H361d Suspected of damaging the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to the central nervous system through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P251 Do not pierce or burn, even after use.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· 2.3 Other hazards**· Results of PBT and vPvB assessment**

This product contains no substance that is considered to be persistent, bioaccumulating or non toxic (PBT). This mixture contains no substance that is considered to be very persistent or very bioaccumulating (vPvB).

· **PBT:** Not applicable.














· **vPvB:** Not applicable.

*** SECTION 3: Composition/information on ingredients****· 3.2 Chemical characterisation: Mixtures**

· **Description:** Mixture of hazardous substances listed below with nonhazardous additions.

Continue on page 4

Trade name: Spray 9910 Underbody

Dangerous components:		
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 RTECS: EJ 4200000	butane, pure  Flam. Gas 1A, H220  Acute Tox. 3, H331 Press. Gas (Comp.), H280 Note: C	20-<25%
CAS: 108-88-3 EINECS: 203-625-9 Index number: 601-021-00-3 RTECS: XS 5250000 Reg.nr.: 01-2119471310-51-0000 01-2119471310-51-0003 01-2119471310-51-0005 01-2119471310-51-0002 01-2119471310-51-0027	toluene  Flam. Liq. 2, H225  Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1, H304  Skin Irrit. 2, H315; STOT SE 3, H336	10-<15%
CAS: 64742-49-0 EINECS: 265-151-9 Index number: 649-328-00-1 Reg.nr.: 01-2119475514-35-0001	Naphtha (petroleum), hydrotreated light  Flam. Liq. 2, H225  Asp. Tox. 1, H304  Aquatic Chronic 2, H411  Skin Irrit. 2, H315; STOT SE 3, H336 Note: P, 4	5-<10%
CAS: 64742-82-1 EINECS: 265-185-4 Index number: 649-330-00-2 Reg.nr.: 01-2119458049-33-0002	Low boiling point hydrogen treated naphtha  Flam. Liq. 3, H226  STOT RE 1, H372; Asp. Tox. 1, H304 Note: P	1-<5%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 RTECS: TZ 4300000	isobutane  Flam. Gas 1A, H220 Press. Gas (Comp.), H280 Note: C	1-<5%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 RTECS: TX 2275000	propane  Flam. Gas 1A, H220 Press. Gas (Comp.), H280	1-<5%

Additional information: For the wording of the listed hazard phrases refer to section 16.

Trade name: Spray 9910 Underbody

*** SECTION 4: First aid measures****4.1 Description of first aid measures**

- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures**5.1 Extinguishing media****Suitable extinguishing agents:**

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

5.3 Advice for firefighters

Firefighters should always protective equipment and breathing apparatus when handling fire coming from these products

5.6 Fire and explosion Hazards**Speial protective equipment and fire fighting procedures:**

Mouth respiratory protective device.

Firefighters should wear full protective flameproof clothing and self contained breathing apparatus for the firefighter if necessary. In the event of any fire try cool down the tanks with water spray. If possible do not allow the water used by firefighters to enter the drains or come in any contact with the water supply lines for the public. Always seek as appropriate.

Additional information Collect contaminated fire fighting water separately. It must not enter the sewage system.

*** SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures**

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Continue on page 6

Trade name: Spray 9910 Underbody

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to section 13.
 Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.
 Open and handle receptacle with care.

Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.
 Keep ignition sources away - Do not smoke.
 Keep respiratory protective device available.
 Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

Information about storage in one common storage facility: Not required.

Further information about storage conditions: Keep container tightly sealed.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

106-97-8 butane, pure

WEL	Short-term value: 1810 mg/m ³ , 750 ppm Long-term value: 1450 mg/m ³ , 600 ppm Carc (if more than 0.1% of buta-1.3-diene)
-----	---

Continue on page 7

Trade name: Spray 9910 Underbody**108-88-3 toluene**

WEL	Short-term value: 384 mg/m ³ , 100 ppm Long-term value: 191 mg/m ³ , 50 ppm Sk
-----	--

· **Regulatory information** WEL: EH40/2020

· **Additional information:** The lists valid during the making were used as basis.

8.2 Exposure controls**Personal protective equipment:****General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the skin.
- Avoid contact with the eyes and skin.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material


The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact in work areas without heightened risk of injury (e.g. Laboratory) gloves made of the following material are suitable:

The breakthrough time of gloves is unknown for this product itself. The glove material that can be used is recommended on the basis of the different substances in the preparation.

Continue on page 8

Trade name: Spray 9910 Underbody

- **For the permanent contact gloves made of the following materials are suitable:** Fluorocarbon rubber (Viton)
 - **For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:**
 Rubber gloves
 - **Eye protection:**
 Safety glasses
- 

Tightly sealed goggles
- **Body protection:** Protective work clothing

*** SECTION 9: Physical and chemical properties**

9.1 Information on basic physical and chemical properties

General Information

Appearance:

- Form:** Aerosol
- Colour:** Black
- Odour:** Characteristic
- Odour threshold:** Not determined.

pH-value: Mixture is non-soluble (in water).

Change in condition

- Melting point/freezing point:** Undetermined.
- Initial boiling point and boiling range:** -44.5 °C

Flash point: < 23 °C

Flammability: Not applicable.

Autoignition temperature: N/A

Decomposition temperature: Not determined.

Ignition temperature: Product is not selfigniting.

Explosive properties: Risk of explosion by shock, friction, fire or other sources of ignition.

Continue on page 9

Trade name: Spray 9910 Underbody

· Explosion limits:	
Lower:	1.2 Vol % (108-88-3 toluene)
Upper:	7 Vol % (108-88-3 toluene)
· Vapour pressure at 20 °C:	29 hPa (108-88-3 toluene)
· Vapour pressure at 50 °C:	124 hPa
· Density at 20 °C:	0.90365 g/cm ³
· Bulk density:	903.7 kg/m ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic at 20 °C:	0 mm ² /s
· Solvent content:	
Organic solvents:	50.2 %
Water:	0.8 %
VOC (EC)	522.3 g/l
Solids content (volume):	41.8 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.

Continue on page 10

Trade name: Spray 9910 Underbody

- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

471-34-1 calcium carbonate

Oral	LD50	6,450 mg/kg (rat)
------	------	-------------------

106-97-8 butane, pure

Inhalative	LC50/4 h	658 mg/l (rat)
------------	----------	----------------

108-88-3 toluene

Oral	LD50	5,000 mg/kg (rat)
Dermal	LD50	12,124 mg/kg (rabbit)
Inhalative	LC50/4 h	5,320 mg/l (mouse)

- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Additional toxicological information:**
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity**
Suspected of damaging the unborn child.
- **STOT-single exposure**
May cause drowsiness or dizziness.
- **STOT-repeated exposure**
May cause damage to the central nervous system through prolonged or repeated exposure.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

Trade name: Spray 9910 Underbody

* **SECTION 12: Ecological information**

· **12.1 Toxicity**

· **Aquatic toxicity:**

This product is not toxic for the aquatic life. Nevertheless do not dispose the product or any cleaning solvents used along with this product into the sea

· **12.2 Persistence and degradability**

This product contains polyesteric molecules and organic solvents and is not known to be bioaccumulative. It can be considered as biodegradable in small quantities. In case of disposal, it should be treated as a hazardous material and should be disposed accordingly. Do not just throw it away

· **12.3 Bioaccumulative potential** No further relevant information available.

· **12.4 Mobility in soil** No further relevant information available.

· **Ecotoxic effects:**

· **Remark:** Harmful to fish

· **Additional ecological information:**

· **General notes:**

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water
 Do not allow product to reach ground water, water course or sewage system, even in small quantities.
 Danger to drinking water if even extremely small quantities leak into the ground.
 Harmful to aquatic organisms

· **12.5 Results of PBT and vPvB assessment**

· **PBT:** This product contains no substance that is considered to be persistent, bioaccumulating or non toxic (PBT).

· **vPvB:** Not applicable.

· **12.6 Other adverse effects** No further relevant information available.

* **SECTION 13: Disposal considerations**

· **13.1 Waste treatment methods**

· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **European waste catalogue**



HP3	Flammable
HP4	Irritant - skin irritation and eye damage
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP10	Toxic for reproduction
HP14	Ecotoxic

Continue on page 12

Trade name: Spray 9910 Underbody

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

* **SECTION 14: Transport information**

· 14.1 UN-Number	
· ADR, IMDG, IATA	UN1950
· 14.2 UN proper shipping name	
· ADR	UN1950 AEROSOLS
· IMDG	AEROSOLS
· IATA	AEROSOLS, flammable
· 14.3 Transport hazard class(es)	
· ADR	
	
· Class	2.5F Gases.
· Label	2.1
· IMDG, IATA	
	
· Class	2.1 Gases.
· Label	2.1
· 14.4 Packing group	
· ADR, IMDG, IATA	Void
· 14.5 Environmental hazards:	Not applicable.
· 14.6 Special precautions for user	Warning: Gases.
· Hazard identification number (Kemler code):	-

Continue on page 13

Trade name: Spray 9910 Underbody

· EMS Number:	F-D,S-U
· Stowage Code	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
· Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· Transport category	2
· Tunnel restriction code	D
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

*** SECTION 15: Regulatory information**

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
None of the ingredients is listed.

Continue on page 14

Trade name: Spray 9910 Underbody

· **Poisons Act**

· **Regulated explosives precursors**

None of the ingredients is listed.

· **Regulated poisons**

None of the ingredients is listed.

· **Reportable explosives precursors**

None of the ingredients is listed.

· **Reportable poisons**

None of the ingredients is listed.

· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the GB CLP regulation.

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labelling:**

toluene
 Naphtha (petroleum), hydrotreated light
 Low boiling point hydrogen treated naphtha

· **Hazard statements**

H222 Extremely flammable aerosol.
 H229 Pressurised container: May burst if heated.
 H315 Causes skin irritation.
 H361d Suspected of damaging the unborn child.
 H336 May cause drowsiness or dizziness.
 H373 May cause damage to the central nervous system through prolonged or repeated exposure.
 H412 Harmful to aquatic life with long lasting effects.

· **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P251 Do not pierce or burn, even after use.
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P405 Store locked up.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Continue on page 15

Trade name: Spray 9910 Underbody

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Directive 2012/18/EU**

- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category** P3a FLAMMABLE AEROSOLS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3, 48

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· **REGULATION (EU) 2019/1148**

· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS
--

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

108-88-3	toluene	3
----------	---------	---

· Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

108-88-3	toluene	3
----------	---------	---

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has been carried out.

* **SECTION 16: Other information**

This information is based on our current knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H331 Toxic if inhaled.

Continue on page 16

Trade name: Spray 9910 Underbody

- H336 May cause drowsiness or dizziness.
H361d Suspected of damaging the unborn child.
H372 Causes damage to organs through prolonged or repeated exposure.
H373 May cause damage to organs through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.

Classification according to Regulation (EC) No 1272/2008


Aerosols, Section 2.3.1

Bridging principles

Skin corrosion/irritation
Reproductive toxicity
Specific target organ toxicity (single exposure)
Specific target organ toxicity (repeated exposure)
Hazardous to the aquatic environment - long-term (chronic)
aquatic hazard

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Contact:

 FRL Chemie Gmbh, Theresienhöhe 28,
80339 Munich, Germany
MADE IN EU - T. +498926201297 - E. info@vollchem.com
web:www.vollchem.com

*** Data compared to the previous version altered.**

Trade name: Spray 9910 Underbody

*** Annex: Exposure scenario****· Short title of the exposure scenario****· Sector of Use**

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· Product category PC9a Coatings and paints, thinners, paint removers**· Process category** PROC7 Industrial spraying**· Article category** AC1 Vehicles**· Environmental release category** ERC5 Use at industrial site leading to inclusion into/onto article**· Technical function** Other**· Description of the activities / processes covered in the Exposure Scenario**

See section 1 of the annex to the Safety Data Sheet.

· Conditions of use According to directions for use.**· Duration and frequency** Frequency of use:**· Physical parameters**

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

· Physical state Aerosol**· Concentration of the substance in the mixture** The substance is main component.**· Used amount per time or activity** Smaller than 100 g per application.**· Other operational conditions****· Other operational conditions affecting environmental exposure** No special measures required.**· Other operational conditions affecting worker exposure**

Avoid contact with the skin.

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

· Other operational conditions affecting consumer exposure No special measures required.**· Other operational conditions affecting consumer exposure during the use of the product**

Not applicable.

· Risk management measures**· Worker protection****· Organisational protective measures**

Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.

· Technical protective measures

Provide explosion-proof electrical equipment.

Continue on page 18

Trade name: Spray 9910 Underbody

Ensure that suitable extractors are available on processing machines

· **Personal protective measures**

Avoid contact with the skin.

Pregnant women should strictly avoid inhalation or skin contact.

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Measures for consumer protection**

Ensure adequate labelling.

Observe consumer information and advice on safe use.

· **Environmental protection measures**

· **Water**

Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point.

· **Soil** The product is only processed over the concrete collecting basin.

· **Disposal measures** Ensure that waste is collected and contained.

· **Disposal procedures**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Waste type** Partially emptied and uncleaned packaging

· **Exposure estimation**

· **Consumer**

This product is to be used by professional technicians only.

Not relevant for this Exposure Scenario.

· **Guidance for downstream users**

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.