

---

**\* SECTION 1: Identification of the substance/mixture and of the company/undertaking****· 1.1 Product identifier****· Trade name: Spray 9932 Epoxy Primer****· Article number:** FRL1196**· UFI:** FN40-H01Y-S00E-JE6U**· 1.2 Relevant identified uses of the substance or mixture and uses advised against****· Life cycle stages** PW Widespread use by professional workers**· Sector of Use**



SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

**· Product category** PC9b Fillers, putties, plasters, modelling clay**· Process category** PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities**· Environmental release category** ERC2 Formulation into mixture**· Article category** AC1 Vehicles**· Application of the substance / the mixture**

Metal surface treatment

Surface protection

**· 1.3 Details of the supplier of the safety data sheet****· Manufacturer/Supplier:** FRL Chemie Gmbh, Theresienhöhe 28,  
80339 Munich, Germany  
MADE IN EU - T. +498926201297 - E. info@vollchem.com  
web:www.vollchem.com**· Further information obtainable from:** FRL Chemie Gmbh, Theresienhöhe 28,  
80339 Munich, Germany  
MADE IN EU - T. +498926201297 - E. info@vollchem.com  
web:www.vollchem.com**· 1.4 Emergency telephone number:**

Regional Medicines and Poisons Information Centre NI

Pharmacy Department, Royal Hospital Suite

Grosvenor Road Belfast

Telephone: +44 28 90 63 2032

Fax: +44 28 90 24 80 30

Emergency telephone: 844 892 0111

E-mail address: nirdic.nirdic@belfasttrust.hscni.net

---

**Trade name: Spray 9932 Epoxy Primer**

---

Members of the public seeking specific information on poisons should contact:  
In England and Wales: NHS 111 - dial 111  
In Scotland: NHS 24 - dial 111

---

**\* SECTION 2: Hazards identification****2.1 Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008**

GHS02 flame

Aerosol 1            H222 Extremely flammable aerosol.  
                          H229 Pressurised container: May burst if heated.



GHS05 corrosion

Eye Dam. 1            H318 Causes serious eye damage.



GHS09 environment

Aquatic Chronic 2    H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2            H315 Causes skin irritation.  
Skin Sens. 1            H317 May cause an allergic skin reaction.  
STOT SE 3            H336 May cause drowsiness or dizziness.

**2.2 Label elements****Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the GB CLP regulation.

**Hazard pictograms**

GHS02



GHS05



GHS07



GHS09

**Signal word** Danger

Continue on page 3

---

**Trade name: Spray 9932 Epoxy Primer**

---

**· Hazard-determining components of labelling:**

butan-1-ol

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight  $\leq 700$ )

propan-2-ol

acetone

**· Hazard statements**

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

**· Precautionary statements**

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**· Additional information:**

Product contains: Reportable explosives precursors. Making available, introduction, possession and use according to Regulation (EU) 2019/1148, Article 9.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

**· 2.3 Other hazards****· Results of PBT and vPvB assessment**

This product contains no substance that is considered to be persistent, bioaccumulating or non toxic (PBT). This mixture contains no substance that is considered to be very persistent or very bioaccumulating (vPvB).
















**· PBT:** Not applicable**· vPvB:** Not applicable

---

**\* SECTION 3: Composition/information on ingredients****· 3.2 Chemical characterisation: Mixtures****· Description:** Mixture of hazardous substances listed below with nonhazardous additions.

Continue on page 4

**Trade name: Spray 9932 Epoxy Primer**

<b>Dangerous components:</b>		
CAS: 115-10-6 EINECS: 204-065-8 Index number: 603-019-00-8 RTECS: PM 4780000	dimethyl ether -----  Flam. Gas 1A, H220  Acute Tox. 2, H330 Press. Gas (Comp.), H280	35-<40%
CAS: 13463-67-7 EINECS: 236-675-5 Index number: 022-006-00-2	titanium dioxide -----  Carc. 2, H351 Note: V, W, 10	10-<15%
CAS: 67-63-0 EINECS: 200-661-7 Index number: 603-117-00-0 RTECS: NT 8050000 Reg.nr.: 01-2119457558-25-0002 01-2119457558-25-0001	propan-2-ol -----  Flam. Liq. 2, H225  Eye Irrit. 2, H319; STOT SE 3, H336	10-<15%
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 RTECS: AL 3150000 Reg.nr.: 01-2119471330-49-0001	acetone -----  Flam. Liq. 2, H225  Eye Irrit. 2, H319; STOT SE 3, H336	5-<10%
CAS: 1330-20-7 Index number: 601-022-00-9	xylene -----  Flam. Liq. 3, H226  Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	≥5-<10%
CAS: 71-36-3 EINECS: 200-751-6 Index number: 603-004-00-6 RTECS: EO 1400000 Reg.nr.: 01-2119484630-38-0000	butan-1-ol -----  Flam. Liq. 3, H226  Eye Dam. 1, H318  Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335 STOT SE 3, H336	5-<10%
CAS: 25068-38-6 NLP: 500-033-5 Index number: 603-074-00-8	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700) -----  Aquatic Chronic 2, H411  Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317 Specific concentration limits: Eye Irrit. 2; H319: C ≥ 5 % Skin Irrit. 2; H315: C ≥ 5 %	≥2.5-<5%
CAS: 1314-13-2 EINECS: 215-222-5 Index number: 030-013-00-7 RTECS: ZH 4810000	zinc oxide -----  Aquatic Acute 1, H400 (M=1); Aquatic Chronic 1, H410 (M=1)	≥2.5-<5%

Continue on page 5

---

**Trade name: Spray 9932 Epoxy Primer**

---

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

---

\* **SECTION 4: First aid measures**

· **4.1 Description of first aid measures**

· **General information:** Immediately remove any clothing soiled by the product.

· **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.

· **After swallowing:** If symptoms persist consult doctor.

· **4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

· **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

---

\* **SECTION 5: Firefighting measures**

· **5.1 Extinguishing media**

· **Suitable extinguishing agents:**

CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **5.2 Special hazards arising from the substance or mixture** No further relevant information available.

· **5.3 Advice for firefighters**

Firefighters should always protective equipment and breathing apparatus when handling fire coming from these products

· **5.6 Fire and explosion Hazards**

· **Speial protective equipment and fire fighting procedures:**

Firefighters should wear full protective flameproof clothing and self contained breathing apparatus for the firefighter if necessary. In the event of any fire try cool down the tanks with water spray. If possible do not allow the water used by firefighters to enter the drains or come in any contact with the water supply lines for the public. Always seek as appropriate.

· **Additional information** Collect contaminated fire fighting water separately. It must not enter the sewage system.

---

\* **SECTION 6: Accidental release measures**

· **6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

Continue on page 6

---

**Trade name: Spray 9932 Epoxy Primer**

---

**6.2 Environmental precautions:**

- Do not allow product to reach sewage system or any water course.
- Inform respective authorities in case of seepage into water course or sewage system.
- Do not allow to enter sewers/ surface or ground water.

**6.3 Methods and material for containment and cleaning up:**

- Use neutralising agent.
- Dispose contaminated material as waste according to section 13.
- Ensure adequate ventilation.

**6.4 Reference to other sections**

- See Section 7 for information on safe handling.
  - See Section 8 for information on personal protection equipment.
  - See Section 13 for disposal information.
- 

**\* SECTION 7: Handling and storage****7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.**Information about fire - and explosion protection:**

- Do not spray onto a naked flame or any incandescent material.
- Keep ignition sources away - Do not smoke.
- Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

**7.2 Conditions for safe storage, including any incompatibilities****Storage:****Requirements to be met by storerooms and receptacles:**

- Observe official regulations on storing packagings with pressurised containers.

**Information about storage in one common storage facility:** Not required**Further information about storage conditions:** Keep container tightly sealed.**7.3 Specific end use(s)** No further relevant information available.

---

**\* SECTION 8: Exposure controls/personal protection****8.1 Control parameters****Ingredients with limit values that require monitoring at the workplace:****115-10-6 dimethyl ether**

WEL	Short-term value: 958 mg/m <sup>3</sup> , 500 ppm Long-term value: 766 mg/m <sup>3</sup> , 400 ppm
-----	-------------------------------------------------------------------------------------------------------

Continue on page 7

---

**Trade name: Spray 9932 Epoxy Primer**


---

**67-63-0 propan-2-ol**

WEL	Short-term value: 1250 mg/m <sup>3</sup> , 500 ppm Long-term value: 999 mg/m <sup>3</sup> , 400 ppm
-----	--------------------------------------------------------------------------------------------------------

**67-64-1 acetone**

WEL	Short-term value: 3620 mg/m <sup>3</sup> , 1500 ppm Long-term value: 1210 mg/m <sup>3</sup> , 500 ppm
-----	----------------------------------------------------------------------------------------------------------

**1330-20-7 xylene**

WEL	Short-term value: 441 mg/m <sup>3</sup> , 100 ppm Long-term value: 220 mg/m <sup>3</sup> , 50 ppm Sk; BMGV
-----	------------------------------------------------------------------------------------------------------------------

**71-36-3 butan-1-ol**

WEL	Short-term value: 154 mg/m <sup>3</sup> , 50 ppm Sk
-----	--------------------------------------------------------

· **Regulatory information** WEL: EH40/2020

**· DNELs**
**ATE (Acute Toxicity Estimates)**

Inhalative	DNELs	116 mg/m <sup>3</sup>
------------	-------	-----------------------

**1330-20-7 xylene**

Inhalative	DNELs	11 mg/m <sup>3</sup> (ATE)
------------	-------	----------------------------

**· Ingredients with biological limit values:**
**1330-20-7 xylene**

BMGV	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid
------	----------------------------------------------------------------------------------------------------------

· **Additional information:** The lists valid during the making were used as basis.

**· 8.2 Exposure controls**
**· Personal protective equipment:**
**· General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.  
 Immediately remove all soiled and contaminated clothing  
 Wash hands before breaks and at the end of work.  
 Avoid contact with the skin.  
 Avoid contact with the eyes and skin.

Continue on page 8

---

**Trade name: Spray 9932 Epoxy Primer**

---

**· Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

**· Protection of hands:**

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

**· Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

**· Penetration time of glove material**

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

**· For the permanent contact in work areas without heightened risk of injury (e.g. Laboratory) gloves made of the following material are suitable:**

The breakthrough time of gloves is unknown for this product itself. The glove material that can be used is recommended on the basis of the different substances in the preparation.

**· For the permanent contact gloves made of the following materials are suitable:** Fluorocarbon rubber (Viton)**· For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:**

Rubber gloves

**· Eye protection:**

Safety glasses



Tightly sealed goggles

**· Body protection:** Protective work clothing

**Trade name: Spray 9932 Epoxy Primer**

**\* SECTION 9: Physical and chemical properties**

<b>9.1 Information on basic physical and chemical properties</b>	
<b>General Information</b>	
<b>Appearance:</b>	
Form:	Aerosol
Colour:	Grey
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	Mixture is non-soluble (in water).
<b>Change in condition</b>	
Melting point/freezing point:	Undetermined
Initial boiling point and boiling range:	-24.9 °C
Flash point:	< 0 °C
Flammability	Not applicable
Autoignition temperature:	425 °C
Decomposition temperature:	Not determined
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Risk of explosion by shock, friction, fire or other sources of ignition.
<b>Explosion limits:</b>	
Lower:	2 Vol % (67-63-0 propan-2-ol)
Upper:	18.6 Vol % (115-10-6 dimethyl ether)
Vapour pressure at 20 °C:	5,200 hPa (115-10-6 dimethyl ether)
Density at 20 °C:	0.89 g/cm <sup>3</sup>
Relative density	Not determined
Vapour density	Not determined
Evaporation rate	Not applicable.
<b>Solubility in / Miscibility with water:</b>	
	Not miscible or difficult to mix.

Continue on page 10

**Trade name: Spray 9932 Epoxy Primer**

<b>Partition coefficient: n-octanol/water:</b>	Not determined
<b>Viscosity:</b>	
<b>Dynamic:</b>	Not determined
<b>Kinematic:</b>	Not determined
<b>Solvent content:</b>	
<b>Organic solvents:</b>	74.4 %
<b>VOC (EC)</b>	662-662.3 g/l
<b>Solids content (volume):</b>	20.0 %
<b>9.2 Other information</b>	No further relevant information available.

**SECTION 10: Stability and reactivity**

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

**\* SECTION 11: Toxicological information**

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

<b>LD/LC50 values relevant for classification:</b>		
<b>ATE (Acute Toxicity Estimates)</b>		
Oral	LD50	12,951 mg/kg (rat)
Dermal	LD50	21,130-21,161 mg/kg (rabbit)
<b>115-10-6 dimethyl ether</b>		
Inhalative	LC50/4 h	308 mg/l (rat)

Continue on page 11

**Trade name: Spray 9932 Epoxy Primer**

<b>13463-67-7 titanium dioxide</b>		
Oral	LD50	>20,000 mg/kg (rat)
Dermal	LD50	>10,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>6.82 mg/l (rat)
<b>67-63-0 propan-2-ol</b>		
Oral	LD50	5,045 mg/kg (rat)
Dermal	LD50	12,800 mg/kg (rabbit)
Inhalative	LC50/4 h	30 mg/l (rat)
<b>67-64-1 acetone</b>		
Oral	LD50	5,800 mg/kg (rat)
Dermal	LD50	20,000 mg/kg (rabbit)
<b>1330-20-7 xylene</b>		
Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)
<b>71-36-3 butan-1-ol</b>		
Oral	LD50	790 mg/kg (rat)
Dermal	LD50	3,400 mg/kg (rabbit)
Inhalative	LC50/4 h	8,000 mg/l (rat)
<b>1314-13-2 zinc oxide</b>		
Oral	LD50	>5,000 mg/kg (rat)

**· Primary irritant effect:**
**· Skin corrosion/irritation**

Causes skin irritation.

**· Serious eye damage/irritation**

Causes serious eye damage.

**· Respiratory or skin sensitisation**

May cause an allergic skin reaction.

**· Additional toxicological information:**
**· CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
**· Germ cell mutagenicity** Based on available data, the classification criteria are not met.

**· Carcinogenicity** Based on available data, the classification criteria are not met.

**· Reproductive toxicity** Based on available data, the classification criteria are not met.

**· STOT-single exposure**

May cause drowsiness or dizziness.

Continue on page 12

---

**Trade name: Spray 9932 Epoxy Primer**

---

- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
  - **Aspiration hazard** Based on available data, the classification criteria are not met.
- 

**\* SECTION 12: Ecological information****· 12.1 Toxicity****· Aquatic toxicity:**

This product is not toxic for the aquatic life. Nevertheless do not dispose the product or any cleaning solvents used along with this product into the sea

**· 12.2 Persistence and degradability**

This product contains polyesteric molecules and organic solvents and is not known to be bioaccumulative. It can be considered as biodegradable in small quantities. In case of disposal, it should be treated as a hazardous material and should be disposed accordingly. Do not just throw it away

**· 12.3 Bioaccumulative potential** No further relevant information available.**· 12.4 Mobility in soil** No further relevant information available.**· Ecotoxicological effects:****· Remark:** Toxic for fish**· Additional ecological information:****· General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

**· 12.5 Results of PBT and vPvB assessment****· PBT:** This product contains no substance that is considered to be persistent, bioaccumulating or non toxic (PBT).**· vPvB:** Not applicable**· 12.6 Other adverse effects** No further relevant information available.**\* SECTION 13: Disposal considerations****· 13.1 Waste treatment methods****· Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

**· European waste catalogue**

HP3	Flammable
-----	-----------



Continue on page 13

**Trade name: Spray 9932 Epoxy Primer**


HP4	Irritant - skin irritation and eye damage
HP7	Carcinogenic
HP14	Ecotoxic

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

\* **SECTION 14: Transport information**

· <b>14.1 UN-Number</b>	
· <b>ADR, IMDG, IATA</b>	UN1950
· <b>14.2 UN proper shipping name</b>	
· <b>ADR</b>	UN1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS
· <b>IMDG</b>	AEROSOLS, MARINE POLLUTANT
· <b>IATA</b>	AEROSOLS, flammable
· <b>14.3 Transport hazard class(es)</b>	
· <b>ADR</b>	
	
· <b>Class</b>	2 5F Gases.
· <b>Label</b>	2.1
· <b>IMDG</b>	
	
· <b>Class</b>	2.1 Gases.
· <b>Label</b>	2.1

**Trade name: Spray 9932 Epoxy Primer**

<p>· <b>IATA</b></p> 	
· <b>Class</b>	2.1 Gases.
· <b>Label</b>	2.1
<p>· <b>14.4 Packing group</b></p>	
· <b>ADR, IMDG, IATA</b>	Void
<p>· <b>14.5 Environmental hazards:</b></p> <p>Product contains environmentally hazardous substances:          reaction product: bisphenol-A-(epichlorhydrin) epoxy resin          (number average molecular weight <math>\leq 700</math>)</p>	
· <b>Marine pollutant:</b>	Symbol (fish and tree)
· <b>Special marking (ADR):</b>	Symbol (fish and tree)
<p>· <b>14.6 Special precautions for user</b></p> <p>Warning: Gases.</p>	
· <b>Hazard identification number (Kemler code):</b>	-
· <b>EMS Number:</b>	F-D,S-U
· <b>Stowage Code</b>	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
· <b>Segregation Code</b>	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
<p>· <b>14.7 Transport in bulk according to Annex II of          Marpol and the IBC Code</b></p>	
	Not applicable

Continue on page 15

**Trade name: Spray 9932 Epoxy Primer**

<b>· Transport/Additional information:</b>	
<b>· ADR</b>	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· Transport category	2
· Tunnel restriction code	D
<b>· IMDG</b>	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
<b>· IATA</b>	
· Remarks:	•3YE
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS

\* **SECTION 15: Regulatory information**

<b>· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture</b>	
None of the ingredients is listed.	
<b>· Poisons Act</b>	
<b>· Regulated explosives precursors</b>	
None of the ingredients is listed.	
<b>· Regulated poisons</b>	
None of the ingredients is listed.	
<b>· Reportable explosives precursors</b>	
67-64-1   acetone	Listed
<b>· Reportable poisons</b>	
None of the ingredients is listed.	
<b>· Labelling according to Regulation (EC) No 1272/2008</b>	
The product is classified and labelled according to the GB CLP regulation.	

Continue on page 16

---

**Trade name: Spray 9932 Epoxy Primer**

---

**Hazard pictograms**

GHS02 GHS05 GHS07 GHS09

**Signal word** Danger**Hazard-determining components of labelling:**

butan-1-ol

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight  $\leq 700$ )

propan-2-ol

acetone

**Hazard statements**

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

**Precautionary statements**

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Directive 2012/18/EU****Named dangerous substances - ANNEX I** None of the ingredients is listed.**Seveso category**

P3a FLAMMABLE AEROSOLS

E2 Hazardous to the Aquatic Environment

**Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t**Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t

Continue on page 17

**Trade name: Spray 9932 Epoxy Primer**

· **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

· **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

· **REGULATION (EU) 2019/1148**

· **Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

· **Annex II - REPORTABLE EXPLOSIVES PRECURSORS**

67-64-1	acetone
---------	---------

· **Regulation (EC) No 273/2004 on drug precursors**

67-64-1	acetone	3
---------	---------	---

· **Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**

67-64-1	acetone	3
---------	---------	---

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has been carried out.

\* **SECTION 16: Other information**

This information is based on our current knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H302 Harmful if swallowed.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H330 Fatal if inhaled.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H351 Suspected of causing cancer.

Continue on page 18

---

**Trade name: Spray 9932 Epoxy Primer**

---

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

**Classification according to Regulation (EC) No 1272/2008**

Aerosols, Section 2.3.1

Bridging principles

Skin corrosion/irritation


Serious eye damage/irritation

Skin sensitisation

Specific target organ toxicity (single exposure)

Hazardous to the aquatic environment - long-term (chronic)  
aquatic hazard

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

**Contact:** FRL Chemie GmbH, Theresienhöhe 28,  
80339 Munich, Germany  
MADE IN EU - T. +498926201297 - E. info@vollchem.com  
web:www.vollchem.com**\* Data compared to the previous version altered.**

---

**Trade name: Spray 9932 Epoxy Primer**

---

**\* Annex: Exposure scenario****· Short title of the exposure scenario****· Sector of Use**

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

**· Product category** PC9b Fillers, putties, plasters, modelling clay**· Process category** PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities**· Article category** AC1 Vehicles**· Environmental release category** ERC2 Formulation into mixture**· Description of the activities / processes covered in the Exposure Scenario**

See section 1 of the annex to the Safety Data Sheet.

**· Conditions of use** According to directions for use.**· Duration and frequency** Frequency of use:**· Physical parameters**

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

**· Physical state** Fluid**· Concentration of the substance in the mixture** The substance is main component.**· Used amount per time or activity** Smaller than 100 g per application.**· Other operational conditions****· Other operational conditions affecting environmental exposure** Use only on hard ground.**· Other operational conditions affecting worker exposure**

Avoid contact with eyes.

Avoid contact with the skin.

Avoid long-term or repeated skin contact.

Do not breathe gas/vapour/aerosol.

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

**· Other operational conditions affecting consumer exposure** No special measures required.**· Other operational conditions affecting consumer exposure during the use of the product**

Not applicable

**· Risk management measures****· Worker protection****· Organisational protective measures**

Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.

Continue on page 20

---

**Trade name: Spray 9932 Epoxy Primer**

---

**· Technical protective measures**

Provide explosion-proof electrical equipment.  
Use product only in enclosed systems.  
Ensure that suitable extractors are available on processing machines

**· Personal protective measures**

Do not inhale gases / fumes / aerosols.  
Avoid contact with the skin.  
Avoid contact with the eyes.  
Tightly sealed goggles  
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.  
Protective gloves  
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

**· Measures for consumer protection**

Ensure adequate labelling.  
Observe consumer information and advice on safe use.

**· Environmental protection measures****· Water**

Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point.  
Do not allow to reach sewage system.  
Generally, prior to the introduction of wastewater into wastewater treatment plants a neutralisation is required.

**· Soil**

Prevent contamination of soil.  
The product is only processed over the concrete collecting basin.

**· Disposal measures** Ensure that waste is collected and contained.**· Disposal procedures**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

**· Waste type** Partially emptied and uncleaned packaging**· Exposure estimation****· Consumer**

This product is to be used by professional technicians only.  
Not relevant for this Exposure Scenario.

**· Guidance for downstream users**

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.