
*** SECTION 1: Identification of the substance/mixture and of the company/undertaking****· 1.1 Product identifier****· Trade name: Spray 9980 Acryl Paint****· Article number:** FRL1192**· UFI:** 9740-Y0M0-700X-7Q9H**· 1.2 Relevant identified uses of the substance or mixture and uses advised against****· Life cycle stages**

PW Widespread use by professional workers

C Consumer use

· Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

SU17 General manufacturing, e.g. machinery, equipment, vehicles, other transport equipment



· Product category PC9a Coatings and paints, thinners, paint removers**· Process category**

PROC9 Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

· Environmental release category ERC12c Use of articles at industrial sites with low release**· Article category**

AC1 Vehicles

AC7 Metal articles

· Application of the substance / the mixture Surface protection**· 1.3 Details of the supplier of the safety data sheet****· Manufacturer/Supplier:** FRL Chemie Gmbh, Theresienhöhe 28,
80339 Munich, Germany
MADE IN EU - T. +498926201297 - E. info@vollchem.com
web:www.vollchem.com**· Further information obtainable from:** FRL Chemie Gmbh, Theresienhöhe 28,
80339 Munich, Germany
MADE IN EU - T. +498926201297 - E. info@vollchem.com
web:www.vollchem.com**· 1.4 Emergency telephone number:**Regional Medicines and Poisons Information Centre NI
Pharmacy Department, Royal Hospital Suite
Grosvenor Road Belfast
Telephone: +44 28 90 63 2032

Trade name: Spray 9980 Acryl Paint

Fax: +44 28 90 24 80 30

Emergency telephone: 844 892 0111

E-mail address: nirdic.nirdic@belfasttrust.hscni.net

Members of the public seeking specific information on poisons should contact:

In England and Wales: NHS 111 - dial 111

In Scotland: NHS 24 - dial 111

*** SECTION 2: Hazards identification****2.1 Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008**

GHS02 flame

Aerosol 1

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.



GHS07

Skin Irrit. 2

H315 Causes skin irritation.

Eye Irrit. 2

H319 Causes serious eye irritation.

STOT SE 3

H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements**Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms

GHS02 GHS07

Signal word Danger**Hazard-determining components of labelling:**

acetone

Solvent naphtha (petroleum), light arom.

Continue on page 3

Trade name: Spray 9980 Acryl Paint

· **Hazard statements**

- H222 Extremely flammable aerosol.
- H229 Pressurised container: May burst if heated.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H412 Harmful to aquatic life with long lasting effects.

· **Precautionary statements**

- P102 Keep out of reach of children.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P251 Do not pierce or burn, even after use.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P405 Store locked up.
- P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Additional information:**

- Product contains: Reportable explosives precursors. Making available, introduction, possession and use according to Regulation (EU) 2019/1148, Article 9.
- EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

- This product contains no substance that is considered to be persistent, bioaccumulating or non toxic (PBT). This mixture contains no substance that is considered to be very persistent or very bioaccumulating (vPvB).

· **PBT:** Not applicable

· **vPvB:** Not applicable














* **SECTION 3: Composition/information on ingredients**

· **3.2 Chemical characterisation: Mixtures**

· **Description:** Mixture of hazardous substances listed below with nonhazardous additions.

Continue on page 4

Trade name: Spray 9980 Acryl Paint

Dangerous components:		
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 RTECS: EJ 4200000	butane, pure  Flam. Gas 1A, H220  Acute Tox. 3, H331 Press. Gas (Comp.), H280 Note: C	25-<30%
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 RTECS: AL 3150000 Reg.nr.: 01-2119471330-49-0001	acetone  Flam. Liq. 2, H225  Eye Irrit. 2, H319; STOT SE 3, H336	15-<20%
CAS: 64742-95-6 EINECS: 265-199-0 Index number: 649-356-00-4 Reg.nr.: 01-2119455851-35-0001	Solvent naphtha (petroleum), light arom.  Flam. Liq. 3, H226  Asp. Tox. 1, H304  Aquatic Chronic 2, H411  Acute Tox. 4, H332; STOT SE 3, H335 STOT SE 3, H336 Note: H, P, 4	10-<15%
CAS: 1330-20-7 Index number: 601-022-00-9	xylene  Flam. Liq. 3, H226  Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	≥10-<15%
CAS: 13463-67-7 EINECS: 236-675-5 Index number: 022-006-00-2	titanium dioxide  Carc. 2, H351 Note: V, W, 10	5-<10%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 RTECS: TZ 4300000	isobutane  Flam. Gas 1A, H220 Press. Gas (Comp.), H280 Note: C	1-<5%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 RTECS: TX 2275000	propane  Flam. Gas 1A, H220 Press. Gas (Comp.), H280	1-<5%

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures
4.1 Description of first aid measures

General information: Immediately remove any clothing soiled by the product.

Continue on page 5

Trade name: Spray 9980 Acryl Paint

- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
 - **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
 - **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. Remove contact lenses in case of eye contamination and irrigate copiously with clean water for at least 15 minutes trying to hold the eye lids open.
 - **After swallowing:** If symptoms persist consult doctor.
 - **4.2 Most important symptoms and effects, both acute and delayed**
Breathing difficulty
Dizziness
Asthma attacks
 - **4.3 Indication of any immediate medical attention and special treatment needed**
Medical supervision for at least 48 hours.
-

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
 - **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
 - **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
 - **5.3 Advice for firefighters**
Firefighters should always use protective equipment and breathing apparatus when handling fire coming from these products
 - **5.6 Fire and explosion Hazards**
 - **Special protective equipment and fire fighting procedures:**
Firefighters should wear full protective flameproof clothing and self contained breathing apparatus for the firefighter if necessary. In the event of any fire try to cool down the tanks with water spray. If possible do not allow the water used by firefighters to enter the drains or come in any contact with the water supply lines for the public. Always seek advice as appropriate.
 - **Additional information** Collect contaminated fire fighting water separately. It must not enter the sewage system.
-

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Dispose contaminated material as waste according to section 13.

Continue on page 6

Trade name: Spray 9980 Acryl Paint

Ensure adequate ventilation.

6.4 Reference to other sections

- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

* **SECTION 7: Handling and storage**

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**
 - Do not spray onto a naked flame or any incandescent material.
 - Keep ignition sources away - Do not smoke.
 - Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
 - Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Not required
- **Further information about storage conditions:** Keep container tightly sealed.
- **7.3 Specific end use(s)** No further relevant information available.

* **SECTION 8: Exposure controls/personal protection**

· **8.1 Control parameters**

· Ingredients with limit values that require monitoring at the workplace:	
106-97-8 butane, pure	
WEL	Short-term value: 1810 mg/m ³ , 750 ppm Long-term value: 1450 mg/m ³ , 600 ppm Carc (if more than 0.1% of buta-1.3-diene)
67-64-1 acetone	
WEL	Short-term value: 3620 mg/m ³ , 1500 ppm Long-term value: 1210 mg/m ³ , 500 ppm
1330-20-7 xylene	
WEL	Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk; BMGV

Continue on page 7

Trade name: Spray 9980 Acryl Paint

· **Regulatory information** WEL: EH40/2020

· **DNELs**

ATE (Acute Toxicity Estimates)

Inhalative	DNELs	43.9 mg/m ³
------------	-------	------------------------

1330-20-7 xylene

Inhalative	DNELs	11 mg/m ³ (ATE)
------------	-------	----------------------------

· **Ingredients with biological limit values:**

1330-20-7 xylene

BMGV	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid
------	--

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- Avoid contact with the eyes and skin.

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Continue on page 8

Trade name: Spray 9980 Acryl Paint

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **For the permanent contact in work areas without heightened risk of injury (e.g. Laboratory) gloves made of the following material are suitable:**

The breakthrough time of gloves is unknown for this product itself. The glove material that can be used is recommended on the basis of the different substances in the preparation.

· **For the permanent contact gloves made of the following materials are suitable:** Fluorocarbon rubber (Viton)

· **For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:**

Rubber gloves

· **Eye protection:**

Safety glasses



Tightly sealed goggles

· **Body protection:** Protective work clothing

* **SECTION 9: Physical and chemical properties**

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:	Aerosol
Colour:	Different according to colouring
Odour:	Characteristic
Odour threshold:	Not determined

· **pH-value:** Mixture is non-soluble (in water).

· **Change in condition**

Melting point/freezing point:	Undetermined
Initial boiling point and boiling range:	-44.5 °C

· **Flash point:** < 0 °C

· **Flammability** Not applicable

Continue on page 9

Trade name: Spray 9980 Acryl Paint

· Autoignition temperature:	365 °C (106-97-8 butane, pure)
· Decomposition temperature:	Not determined
· Ignition temperature:	Product is not selfigniting.
· Explosive properties:	Risk of explosion by shock, friction, fire or other sources of ignition.
· Explosion limits:	
Lower:	0.7 Vol % (64742-95-6 Solvent naphtha (petroleum), light arom.)
Upper:	13 Vol % (67-64-1 acetone)
· Vapour pressure at 20 °C:	2,100 hPa (106-97-8 butane, pure)
· Density at 20 °C:	0.7-1.15 g/cm ³
· Relative density	Not determined
· Vapour density	Not determined
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined
· Viscosity:	
Dynamic:	Not determined
Kinematic:	Not determined
· Solvent content:	
Organic solvents:	75 %
VOC (EC)	549.7-903.1 g/l
Solids content (volume):	13-23 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

 · **10.1 Reactivity** No further relevant information available.

Continue on page 10

Trade name: Spray 9980 Acryl Paint

- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

* **SECTION 11: Toxicological information**

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:		
ATE (Acute Toxicity Estimates)		
Dermal	LD50	17,210-17,216 mg/kg
106-97-8 butane, pure		
Inhalative	LC50/4 h	658 mg/l (rat)
67-64-1 acetone		
Oral	LD50	5,800 mg/kg (rat)
Dermal	LD50	20,000 mg/kg (rabbit)
64742-95-6 Solvent naphtha (petroleum), light arom.		
Oral	LD50	>6,800 mg/kg (rat)
Dermal	LD50	>3,400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)
1330-20-7 xylene		
Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)
13463-67-7 titanium dioxide		
Oral	LD50	>20,000 mg/kg (rat)
Dermal	LD50	>10,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>6.82 mg/l (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation**
 Causes skin irritation.

Trade name: Spray 9980 Acryl Paint

- **Serious eye damage/irritation**
Causes serious eye irritation.
 - **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
 - **Additional toxicological information:**
 - **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
 - **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
 - **Carcinogenicity** Based on available data, the classification criteria are not met.
 - **Reproductive toxicity** Based on available data, the classification criteria are not met.
 - **STOT-single exposure**
May cause drowsiness or dizziness.
 - **STOT-repeated exposure** Based on available data, the classification criteria are not met.
 - **Aspiration hazard** Based on available data, the classification criteria are not met.
-

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:**
This product is not toxic for the aquatic life. Nevertheless do not dispose the product or any cleaning solvents used along with this product into the sea
- **12.2 Persistence and degradability**
This product contains polyesteric molecules and organic solvents and is not known to be bioaccumulative. It can be considered as biodegradable in small quantities. In case of disposal, it should be treated as a hazardous material and should be disposed accordingly. Do not just throw it away
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Harmful to aquatic organisms
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** This product contains no substance that is considered to be persistent, bioaccumulating or non toxic (PBT).
- **vPvB:** Not applicable

Continue on page 12

Trade name: Spray 9980 Acryl Paint

· **12.6 Other adverse effects** No further relevant information available.

* **SECTION 13: Disposal considerations**

· **13.1 Waste treatment methods**

· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **European waste catalogue**

HP3	Flammable
HP4	Irritant - skin irritation and eye damage
HP7	Carcinogenic
HP14	Ecotoxic

· **Uncleaned packaging:**

· **Recommendation:** Disposal must be made according to official regulations.

* **SECTION 14: Transport information**

· **14.1 UN-Number**

· **ADR, IMDG, IATA** UN1950

· **14.2 UN proper shipping name**

· **ADR** UN1950 AEROSOLS
 · **IMDG** AEROSOLS
 · **IATA** AEROSOLS, flammable

· **14.3 Transport hazard class(es)**


· **ADR**



· **Class** 2.5F Gases.

Continue on page 13

Trade name: Spray 9980 Acryl Paint

· Label	2.1
· IMDG, IATA	
	
· Class	2.1 Gases.
· Label	2.1
· 14.4 Packing group	
· ADR, IMDG, IATA	Void
· 14.5 Environmental hazards:	
Not applicable	
· 14.6 Special precautions for user	
· Hazard identification number (Kemler code):	Warning: Gases.
· EMS Number:	-
· Stowage Code	F-D,S-U
· Segregation Code	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 1. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	
Not applicable	
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity

Continue on page 14

Trade name: Spray 9980 Acryl Paint

· Transport category	2
· Tunnel restriction code	D
<hr/>	
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

* **SECTION 15: Regulatory information**

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
None of the ingredients is listed.

· Poisons Act
· Regulated explosives precursors
None of the ingredients is listed.

· Regulated poisons
None of the ingredients is listed.

· Reportable explosives precursors	
67-64-1 acetone	Listed

· Reportable poisons
None of the ingredients is listed.

· Labelling according to Regulation (EC) No 1272/2008
The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms
 
GHS02 GHS07

· Signal word Danger

Trade name: Spray 9980 Acryl Paint

· **Hazard-determining components of labelling:**

acetone
 Solvent naphtha (petroleum), light arom.

· **Hazard statements**

H222 Extremely flammable aerosol.
 H229 Pressurised container: May burst if heated.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.
 H412 Harmful to aquatic life with long lasting effects.

· **Precautionary statements**

P102 Keep out of reach of children.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P251 Do not pierce or burn, even after use.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P405 Store locked up.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **Seveso category** P3a FLAMMABLE AEROSOLS

· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t

· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t

· **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

· **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

· **REGULATION (EU) 2019/1148**

· **Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

· **Annex II - REPORTABLE EXPLOSIVES PRECURSORS**

67-64-1	acetone
---------	---------

Continue on page 16

Trade name: Spray 9980 Acryl Paint

Regulation (EC) No 273/2004 on drug precursors		
67-64-1	acetone	3
Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors		
67-64-1	acetone	3

15.2 Chemical safety assessment: A Chemical Safety Assessment has been carried out.

*** SECTION 16: Other information**


This information is based on our current knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H331 Toxic if inhaled.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H351 Suspected of causing cancer.
- H411 Toxic to aquatic life with long lasting effects.

Classification according to Regulation (EC) No 1272/2008	
Aerosols, Section 2.3.1	Bridging principles
Skin corrosion/irritation Serious eye damage/irritation Specific target organ toxicity (single exposure) Hazardous to the aquatic environment - long-term (chronic) aquatic hazard	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Contact:

 FRL Chemie Gmbh, Theresienhöhe 28,
80339 Munich, Germany
MADE IN EU - T. +498926201297 - E. info@vollchem.com
web:www.vollchem.com

Trade name: Spray 9980 Acryl Paint

· * **Data compared to the previous version altered.**

Trade name: Spray 9980 Acryl Paint

*** Annex: Exposure scenario****· Short title of the exposure scenario****· Sector of Use**

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

SU17 General manufacturing, e.g. machinery, equipment, vehicles, other transport equipment

· Product category PC9a Coatings and paints, thinners, paint removers**· Process category**

PROC9 Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

· Article category

AC1 Vehicles

AC7 Metal articles

· Environmental release category ERC12c Use of articles at industrial sites with low release**· Description of the activities / processes covered in the Exposure Scenario**

See section 1 of the annex to the Safety Data Sheet.

· Conditions of use According to directions for use.**· Duration and frequency** Frequency of use:**· Physical parameters**

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

· Physical state Aerosol**· Concentration of the substance in the mixture** The substance is main component.**· Used amount per time or activity** Smaller than 100 g per application.**· Other operational conditions****· Other operational conditions affecting environmental exposure**

No special measures required.

Use only on hard ground.

· Other operational conditions affecting worker exposure

Avoid contact with eyes.

Avoid contact with the skin.

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

· Other operational conditions affecting consumer exposure No special measures required.**· Other operational conditions affecting consumer exposure during the use of the product**

Not applicable

Continue on page 19

Trade name: Spray 9980 Acryl Paint

· Risk management measures**· Worker protection****· Organisational protective measures**

Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.

· Technical protective measures

Provide explosion-proof electrical equipment.

Use product only in enclosed systems.

Ensure that suitable extractors are available on processing machines

· Personal protective measures

Avoid contact with the skin.

Avoid contact with the eyes.

Tightly sealed goggles

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Measures for consumer protection

Ensure adequate labelling.

Observe consumer information and advice on safe use.

· Environmental protection measures**· Water**

Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point.

Do not allow to reach sewage system.

· Soil

Prevent contamination of soil.

The product is only processed over the concrete collecting basin.

· Disposal measures Ensure that waste is collected and contained.**· Disposal procedures**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Waste type Partially emptied and uncleaned packaging**· Exposure estimation****· Consumer**

This product is to be used by professional technicians only.

The highest inhalative exposure to be expected for consumers is 1000 ppm.

Continue on page 20

Trade name: Spray 9980 Acryl Paint

The highest dermal exposure to be expected for consumers is 1000 mg / kg / day.

The highest oral exposure to be expected for consumers is 1000 mg / kg / day.

Guidance for downstream users

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.