



PRODUCT DATA SHEET

9110 BITUMEN UNDERBODY PROTECTION

PRODUCT DESCRIPTION:

Bitumen based underbody coating that provides a durable protection against stone chip and corrosion. Can not be overpainted. Ready for use product

SUBSTRATES:

Underbody car parts

SUBSTRATE PREPARATION:



Surfaces must be clean, dry, and free of rust, dust, and grease. Before the application use 9651 degreaser.

APPLICATION:



Always wear protective equipment



Shake before use



4 - 5 mm
5 - 6 bar (73 - 87 psi)



10 - 15 min / 23°C (73°F)



2 - 6 h / 23°C (73°F)
30 min / 60°C (140°F)



Protect from humidity



Close container tightly

PRODUCT DATA SHEET

9110 BITUMEN UNDERBODY PROTECTION

EQUIPMENT CLEANING:

After use, clean all equipment thoroughly with Nitro Thinner.

TYPICAL PRODUCT DATA:

SPECIFIC GRAVITY: 1,0 - 1,2g/cm³

SOLIDS CONTENT: 68% ± 2%

THEORETICAL COVERAGE: 4 - 5 m² / l at 100 µm

VOC INFORMATION: 2004/42/IB(e) (840)840

COLOUR: BLACK

PACKSIZE: 1L

STORAGE CONDITIONS: Store in cool place (5°- 25°C), avoid direct exposure to sunlight.

SHELF LIFE: 24 months in tightly closed containers

For professional use only! These products are not to be used for purposes other than those specified. The information on this TDS is based on present scientific and technical knowledge, and it is the responsibility of the user to take all necessary steps to ensure the suitability of the product for the intended purpose. We are not liable for its correctness, accuracy and completeness.

All rights reserved. The user of this product should use the product in accordance with the laws and regulations for safety at work and waste management. We reserve the right to modify and to complete the information content at any time, without prior notice or obligation to update.

JUNE 2023