



PRODUCT DATA SHEET

# 9160 SEAM SEALER

**PRODUCT DESCRIPTION:**

A synthetic rubber-based sealant, swiftly dries to form a flexible cord resilient to both heat and cold (ranging from -25°C to +80°C). This coating, impermeable to water and mineral spirits, is ideal for waterproof sealing of joints, especially when installing aftermarket body parts or covering trim pieces in areas slated for future painting. Moreover, it serves as body protection for welding seams, functioning as a thixotropic sealant and anticorrosive pasty material with excellent metal surface adhesion. It must not be directly exposed to UV light. Additionally, it allows immediate recoating with “wet-on-wet” synthetic paints or, after drying, with single or two-component acrylic paints.

**SUBSTRATES:**

Doors, hood, and side panels as well as the external undercarriage sections of the vehicle.

**SUBSTRATE PREPARATION:**



Surfaces must be clean, dry, and free of rust, dust, and grease. Before the application use 9651 Silicone Degreaser.

**APPLICATION:**



Always wear protective equipment



Apply using the cartridge



15 - 20 min / 23°C (73°F)  
Final flash off time



Drying time  
200 µm (8 mil) = 2 - 3h /  
23°C (73°F)



After dry time It can be painted over with primers or 1K basecoat and 2K topcoats

**REMARKS**

For better adhesion, it is recommended prior to painting, the use of 9355 Plastic Primer



Close container tightly

PRODUCT DATA SHEET

# 9160 SEAM SEALER

---

**EQUIPMENT CLEANING:**

After use, clean all equipment thoroughly with Nitro Thinner.

**TYPICAL PRODUCT DATA:**

**SPECIFIC GRAVITY:**  $1.1 \pm 0.05 \text{ g/cm}^3$

**SOLIDS CONTENT:**  $64 \pm 2\%$

**VOC INFORMATION:** 2004/42/IB(e) (840)840

**COLOUR:** BEIGE

**PACKSIZE:** 300ml

**STORAGE CONDITIONS:** Store in cool place (5°- 25°C), avoid direct exposure to sunlight.

**SHELF LIFE:** 24 months in tightly closed containers

For professional use only! These products are not to be used for purposes other than those specified. The information on this TDS is based on present scientific and technical knowledge, and it is the responsibility of the user to take all necessary steps to ensure the suitability of the product for the intended purpose. We are not liable for its correctness, accuracy and completeness.

All rights reserved. The user of this product should use the product in accordance with the laws and regulations for safety at work and waste management. We reserve the right to modify and to complete the information content at any time, without prior notice or obligation to update.

APRIL 2024