



PRODUCT DATA SHEET

9410 UHS SR CLEARCOAT

PRODUCT DESCRIPTION:

2K scratch-resistant UHS Clearcoat, boasting excellent flow properties and impressive UV resistance. Its application is effortless, yielding a high gloss finish. Versatile in use, it is suitable for spot, panel, and overall repairs.

SUBSTRATES:

Solvent- and waterbased basecoat paints.

SUBSTRATE PREPARATION:

The surface of the basecoat must be dry and free of dust. Clean the surface with a tack cloth prior to clearcoat application.

APPLICATION:



Always wear protective equipment



2 parts 9410
1 part 9511 SLOW / 9512 STANDARD / 9513 FAST
Pot life: 1.5 - 3.5 h / 23°C (73°F)



10% 9612 STANDARD



17 - 19s
DIN 4 / 20°C (68°F)



Gravity spraygun nozzle
1.2 - 1.3 mm
Pressure 1.7 - 2.2 bar (25 - 32 psi)
Film Thickness 2x = 50 - 60 µm (2 - 2.4 mil)



5 - 10 min / 23°C (73°F)



8 - 16 hrs / 23°C (73°F)
20 - 30 min / 60°C (140°F)



Short wave 8 - 12 min
Lamp distance: 70 - 80 cm
Do not expose the surface to temperatures above 80°C (176°F).

PRODUCT DATA SHEET

9410 UHS SR CLEARCOAT

EQUIPMENT CLEANING:

After use, clean all equipment thoroughly with 9612 STANDARD or Nitro Thinner.

TYPICAL PRODUCT DATA:

SPECIFIC GRAVITY: 0.95 ± 0.01 g/cm³

SOLIDS CONTENT: 50 ± 2% Weight

VOC INFORMATION: 2004/42/IIIB(e) (840)840

COLOUR: TRANSPARENT

PACKSIZE: 1L, 5L

STORAGE CONDITIONS: Store in a cool place (5–25°C / 41–77°F), avoid direct exposure to sunlight.

SHELF LIFE: 24 months in tightly closed containers.

2K paint systems are moisture-sensitive; therefore, all equipment used must be completely free of water. Isocyanates may cause skin sensitization, so appropriate precautions should always be taken during handling. Individuals with a history of allergic (histaminic) conditions or respiratory disorders are advised to consult a doctor prior to use.

For professional use only! These products are not to be used for purposes other than those specified. The information on this TDS is based on present scientific and technical knowledge, and it is the responsibility of the user to take all necessary steps to ensure the suitability of the product for the intended purpose. We are not liable for its correctness, accuracy and completeness.

All rights reserved. The user of this product should use the product in accordance with the laws and regulations for safety at work and waste management. We reserve the right to modify and to complete the information content at any time, without prior notice or obligation to update.

APRIL 2026