



PRODUCT DATA SHEET

SPRAY 9982 BUMPER PAINT TEXTURE

PRODUCT DESCRIPTION:

A quick-drying acrylic textured paint formulated for plastic parts, providing excellent coverage. It is suitable for direct application on all plastic surfaces, except for PE (Polyethylene)

SUBSTRATES:

Plastic parts except PE

SUBSTRATE PREPARATION:



Surfaces must be clean, dry, and free of rust, dust, and grease. Before the application use 9651 Silicone degreaser.

APPLICATION:



Shake the can well before use 2 - 3 min.



Spray the paint from approximately 20 - 30 cm away from the surface.



Apply 2 - 3 thin coats.



5 - 10 min / 23°C (73°F)



10 min / 23°C (73°F) Dust free
24h / 23°C (73°F) Full hardness



After use, simply invert the can and spray to clear any residue.

PRODUCT DATA SHEET

SPRAY 9982 BUMPER PAINT TEXTURE

TYPICAL PRODUCT DATA:

SPECIFIC GRAVITY: $0.8 \pm 0.02 \text{ g/cm}^3$

SOLIDS CONTENT: $20 \pm 0.02\%$ Weight

VOC INFORMATION: 2004/42/IB(e) (840)840

COLOUR: BLACK, GREY

PACKSIZE: 400ml

STORAGE CONDITIONS: Store in cool place (5 - 25°C), avoid direct exposure to sunlight.

SHELF LIFE: 36 months in tightly closed containers

These products are not to be used for purposes other than those specified. The information on this TDS is based on present scientific and technical knowledge, and it is the responsibility of the user to take all necessary steps to ensure the suitability of the product for the intended purpose. We are not liable for its correctness, accuracy and completeness.

All rights reserved. The user of this product should use the product in accordance with the laws and regulations for safety at work and waste management. We reserve the right to modify and to complete the information content at any time, without prior notice or obligation to update.

JUNE 2025